


Manufacturer	Shockwave Karting, Inc
Chassis model	DD2-1
Category	ROTAX MAX Challenge, 125 MAX DD2 class
Validity of approval	without limitation
Date of approval by BRP-ROTAX	2007 04 04

Technical definiton of the frame Built according to CIK regualtions for short circuits karts

Technical definition of the components of the chassis		
Brake system:	Designed according to CIK rules for shifter classes.	
	A brake system with a valid CIK Homologation must be used.	
Bodywork:	Designed according to CIK rules for short circuit karts.	
	A bodywork with a valid CIK Homologation must be used.	
Rear Tire Protection System:	: For the participation at national or internatioinal ROTAX MAX	
	Challenge race, the ROTAX Rear Tire Protection System must be used.	



Technical description	Dimensions	Tolerance
Outer diameter of the main tubes (without painting)	30.0mm	+/- 0,5 mm
Rear width of main tubes (center line to center line)	610.0 mm	+/- 5,0 mm
Distance of the rear two main tubes on the right side (center	90.0 mm	+/- 0,5 mm
line to center line)		
Wheelbase	1040 mm	+/- 5,0 mm

Technical description	Figure
Number of adjustable/removeable stabilizers at the frame	2

BRP-ROTAX CHASSIS APPROVAL FORM



BRP-ROTAX CHASSIS APPROVAL FORM

